

Point Source Irrigation



233AF (Anti Frost) Bayonet

Performance Table

Single nozzle			
Nozzle	PSI	GPM	Dia. Feet
9/64" Blue	30	2.93	85
	40	3.38	86
	50	3.78	87
	60	4.14	88
	70	4.47	90
5/32" Black	80	4.72	96
	30	3.81	85
	40	4.40	90
	50	4.92	92
	60	5.39	98
11/64" Brown	70	5.82	101
	80	6.25	101
	30	4.48	87
	40	5.18	93
	50	5.79	94
13/64" Purple	60	6.34	96
	70	6.85	105
	80	7.64	105
	30	5.83	88
	40	6.73	95
7/32" Orange	50	7.53	98
	60	8.24	110
	70	8.90	111
	80	9.72	114
	30	7.17	89
15/64" Red	40	8.28	98
	50	9.26	105
	60	10.15	110
	70	10.96	116
	80	11.57	118
1/4" Gray	30	8.51	94
	40	9.84	100
	50	11.00	108
	60	12.05	112
	70	13.02	117
	80	13.88	118
	30	9.82	107
	40	11.35	111
	50	12.69	112
	60	13.90	113
	70	15.00	123
	80	16.20	123

Color Codes are for main nozzles

Two nozzles			
Nozzle	PSI	GPM	Dia. Feet
9/64"x3/32" Blue	30	4.21	85
	40	4.86	86
	50	5.44	87
	60	5.96	88
	70	6.42	90
5/32"x3/32" Black	80	6.80	96
	30	5.06	85
	40	5.85	90
	50	6.54	92
	60	7.17	93
11/64"x3/32" Brown	70	7.74	96
	80	8.32	101
	30	5.74	87
	40	6.63	93
	50	7.41	94
13/64"x3/32" Purple	60	8.12	96
	70	8.77	105
	80	9.72	105
	30	7.08	88
	40	8.18	95
7/32"x3/32" Orange	50	9.15	98
	60	10.02	110
	70	10.82	111
	80	11.80	114
	30	8.43	89
15/64"x3/32" Red	40	9.74	98
	50	10.88	105
	60	11.93	110
	70	12.88	116
	80	13.65	118
1/4"x1/8" Gray	30	9.77	94
	40	11.29	100
	50	12.62	108
	60	13.83	112
	70	14.94	117
	80	15.97	118
	30	11.63	107
	40	13.43	111
	50	15.02	112
	60	16.45	113
	70	17.77	123
	80	19.20	123

The 3/32" back slotted nozzle is Gray



Point Source Irrigation
2550 S. East Ave.
Suit 120
Fresno, CA 93706

Tel: (559) 498-6800
Fax: (559) 498-6886