





































ABS SOLVENT CEMENTS		Max Pipe Size (Interference Fit)	Set Time	Available Color	Industry Listing	Meets Following Performance Specification	Medium Bodied
	771™ ABS <ul style="list-style-type: none"> For plumbing applications (DWV, sewer & drain pipe), conduit and foam core. 	<ul style="list-style-type: none"> 8" (200 mm) ABS 	Fast	 	  	ASTM D 2235 NSF/ANSI 14 CSA B181.1	
	773™ ABS <ul style="list-style-type: none"> For plumbing applications (DWV, sewer & drain pipe), conduit and foam core. 	<ul style="list-style-type: none"> 8" (200 mm) ABS 	Fast		 	ASTM D 2235 NSF/ANSI 14	

TRANSITION & SPECIALTY SOLVENT CEMENTS							
	763™ STYRENE <ul style="list-style-type: none"> High-strength styrene rubber cement for styrene rubber plastic drain and sewer pipe and fittings. Can also be used on styrene vacuum pipe systems. Do not use this cement for other plastic types. 	<ul style="list-style-type: none"> 6" (160 mm) Styrene 	Fast		—	ASTM D 2852	Medium Bodied
	790™ MULTI-PURPOSE <ul style="list-style-type: none"> High-strength multi-purpose cement for PVC and CPVC pipe and fittings. Can be used on ABS and Styrene low-pressure systems. 	<ul style="list-style-type: none"> 6" (160 mm) 4" (110 mm) Schedule 80-PN 10 & 16 	Fast		—	ASTM D 2564 ASTM D 2235 ASTM F 493	
	794™ ABS - PVC <ul style="list-style-type: none"> For use only on ABS to PVC transition joints in non-pressure systems. Suitable for sewer, DWV and conduit. 	<ul style="list-style-type: none"> 6" (160 mm) <u>Not</u> for Schedule 80-PN 10 or higher 	Fast		 	ASTM D 3138	

PRIMERS & CLEANERS				Available Color	Industry Listing	Meet Following Performance Specification
	P-68™ PRIMER <ul style="list-style-type: none"> Quality primer essential for proper softening and preparation of PVC and CPVC pipe and fitting surfaces. 			 	 	ASTM F 656 NSF/ANSI 14 NSF/ANSI 61
	P-70™ PRIMER <ul style="list-style-type: none"> Premium industrial strength primer essential for proper softening and preparation of PVC and CPVC pipe and fitting surfaces. Specially recommended for use on Schedule 80 (PN 10 and higher) and large size pipe. Excellent for cold weather applications. 			 	 	ASTM F 656 NSF/ANSI 14 NSF/ANSI 61
	P-75™ PRIMER <ul style="list-style-type: none"> Premium, fast acting, industrial strength primer essential for proper softening and preparation of PVC and CPVC pipe and fitting surfaces. Specially formulated for wet and/or quick set applications. 					ASTM F 656 NSF/ANSI 14 NSF/ANSI 61
	PC-64™ PRIMER/CLEANER <ul style="list-style-type: none"> For cleaning and surface preparation of PVC and CPVC pipe and fittings before bonding with solvent cements. 			 	—	—
	C-65™ CLEANER <ul style="list-style-type: none"> For removal of oil and grease from the surfaces of PVC, CPVC, ABS and STYRENE pipe and fittings for bonding. Recommended for use before priming of pipe and fittings. 				—	—